ELD79-LGD2006 Transformation Techniques Implementation and Accuracy Comparison in Tripoli Area, Libya

Jamal A. Gledan, Othman A. Azzeidani

Abstract—During the last decade, Libya established a new Geodetic Datum called Libyan Geodetic Datum 2006 (LGD 2006) by using GPS, whereas the ground traversing method was used to establish the last Libyan datum which was called the Europe Libyan Datum 79 (ELD79). The current research paper introduces ELD79 to LGD2006 coordinate transformation technique, the accurate comparison of transformation between multiple regression equations and the three – parameters model (Bursa-Wolf). The results had been obtained show that the overall accuracy of stepwise multi regression equations is better than that can be determined by using Bursa-Wolf transformation model.

Keywords—Geodetic datum, horizontal control points, traditional similarity transformation model, unconventional transformation techniques.

I. INTRODUCTION

THE first datum of Libya, defined for geodetic network and mapping, is ELD79 based on Hayford International Ellipsoid 1924 (a = 6378388, f =1/297). In the1980's, Libya established Doppler network, which was initially defined in the WGS-72 datum and then in the International Terrestrial Reference Frame 2000 (ITRF00) datum.

Later, Surveying Department of Libva SDL introduced LGD2006, again based on Hayford International ellipsoid 1924 (a = 6378388, f = 1/297), for this purpose some of 61 stations were GPS surveyed in 2006 and tied to IGS stations (Epoch: 2006.3822). Thus, precise coordination, were determined in the ITRF00 datum, based on GRS80 ellipsoid (a=6378137.0 m, f=1/298.25722101) [8]. Libya's datum information is illustrated in Table I. Fig. 1 shows the distribution of the first order control points [8] (the main geodetic control points in LGD2006 datum). The issue of datum transformation of control points, coordination of the old geodetic datum ELD79 to the new geodetic datum LGD2006, is a crucial dilemma. The transformation will help GPS users to utilize with the ELD79 control points for their works. Also it can transfer almost of the surveying works e.g. maps which made before 2006 from old datum to new one. The origin of one coordination system is assumed to be offset from the other, the axes of one coordinate system are assumed to be

parallel with respect to the other, and the two systems are assumed to have no different scales.

The most widely used traditional methods are Bursa-Wolf and Molodensky-Badekas transformations. Regarding these traditional methods, it is impossible to make uniform transformation for the whole area of the country because the attainable accuracy is not sufficient [6]. Furthermore, the traditional methods do not take into account the systematic errors existing in the national geodetic networks [2]. With Multiple Regression Equations better results could be obtained.

TABLE I Libyan Horizontal and Vertical Datum

EIBTAIL HORIZOITTIE AND VERTICAE BATOM			
Datum type	Name	Description	Reference
Horizontal	ELD79/LG	Haford international 1924	SDL Datum
datum	D2006	a=6378388,f=1/297	report
Vertical		Mean Sea Level of	SDL Datum
Datum		Mediterranean Sea (MSL)	report
Horizontal	ITDE00	GRS80 (a=6378137,	SDL Datum
Datum	11KF00	f=1/298.25722101)	report
Vertical		Mean Sea Level of	SDL Datum
Datum		Mediterranean Sea (MSL)	report



Fig. 1 The main geodetic control points in LGD2006

II. DATUM TRANSFORMATION TECHNIQUES

A. Traditional Similarity Transformation Model

There are several transformation models such as Bursa-Wolf, Molodensky-Badekas, Veis Model, Thomson-Krakiwsky Model, Helmert Similarity Transformation and

Jamal A. Gledan is Assistant professor, Department of Civil Engineering, Tripoli University, Tripoli, Libya (phone: 00218-91-1542084; e-mail: jamalgledan@hotmail.com).

Othman A. Azzeidani is Msc Candidate, Department of Civil Engineering, Tripoli University, Tripoli, Libya (phone: 00218-92-6832164; e-mail: Othman.mahdi@ yahool.com).

Affine transformation. They are also called similarity or seven-parameter transformations. Each of these models could be used to determine parameters necessary to convert data in a geodetic datum into another datum and vice versa.

Generally, the similarity transformation model is based on 7 parameter; three translation parameters (dx, dy, and dz), three rotation parameters (ωx , ωy , and ωz), and a parameter (s) for the scale difference between two systems. Three –parameters Bursa-Wolf model [5], [3] are used in this research because the relationship between LGD2006 and ELD79 is based on 3 parameters (dx, dy, and dz). This model simply applies three-dimensional origin shift, with little regard to any scale changes or rotations. Therefore, it is coarse, but also extremely simple to implement. The Cartesian coordination of the initial datum are simply added to the origin shift, and then converted to curvilinear coordinates on the new datum. In vector form, this can be as follows [9]:

$$\begin{bmatrix} X \\ Y \\ Z \end{bmatrix}_{W} = \begin{bmatrix} X_{0} \\ Y_{0} \\ Z_{0} \end{bmatrix} + \begin{bmatrix} X \\ Y \\ Z \end{bmatrix}_{A}$$
(1)

B. Unconventional Transformation Techniques

The stepwise multiple regression technique [4] is the other technique used to determine the transformation parameters between ELD79 datum and LGD200 datum. This technique is based on modeling the differences $\Delta \phi$, $\Delta \lambda$ and Δh between two geodetic systems.

The general form of the stepwise multiple regression equation for datum transformation is [1]:

$$\Delta \phi = A_0 + A_1 \phi + a_2 \lambda + A_3 \phi_2 + A_4 \phi \lambda + A_5 \lambda_2 + \dots + A_{99} \phi_9 \lambda_9$$
(2)

where:

 $A_0, A_1,..., A_{99}$ = coefficients determined in the development ϕ, λ = geodetic latitude and geodetic longitude (in degrees), Respectively, of the computation point

Similar equations are obtained for $\Delta\lambda$ and Δh by replacing $\Delta\phi$ in the left portion of (2) by $\Delta\lambda$ and Δh , respectively.

The first step of the procedure produces a constant and a variable. The procedure then sequentially adds one variable at a time to the equation and the variable that provides the greatest improvement in fitting the coordinate difference. After a variable had been added, all variables previously incorporated into the equation are tested, if one is no longer significant, it is removed. Each addition or removal of a variable is called a "step". This stepwise addition or removal of variables ensures that only significant variables are retained in the final equation.

III. DATA USED AND RESULTS

Precise geodetic coordinates of 30 first-order geodetic stations known in both ELD79 and LGD2006 geodetic datum, (all these 30 first-order geodetic stations known are located in zone 7 ,which extend from 12° E to 14° E), have been used in

this investigation and four stations have been considered as check points, that haven't been used in the processing stage. These coordinates are the most accurate database available in Surveying Department of Libya SDL for this zone. The following are the results obtained by using two methods, three-parameters Bursa-Wolf model and stepwise multiple regression equations.

A. Results of the Three –Parameters (Bursa-Wolf) Model

The final results by using the first method of transformation technique (the three-parameter) Bursa-Wolf model for ELD79-LGD2006 transformation are:

$$\Delta X = +94.2048$$
(3)

$$\Delta Y = + 11.4361 \tag{4}$$

$$\Delta Z = -149.582$$
 (5)

B. Results of Stepwise Multiple Regression Technique

The final stepwise multiple regression formulas for transforming coordinates from the ELD79 to the LGD2006 system, (formula for Δ h is excluded in this research) are:

$$\Delta \phi'' = 6.255 + 3.532 E^{-17} \lambda_{79}^{13} - 8.091 E^{-21} \phi_{79}^{13} - 7.187 E^{-5} \phi_{79}^{2} \lambda_{79} + 1.831 E^{-15} \phi_{79}^{9} \lambda_{79} - 7.088 E^{-21} \phi^{12} \lambda$$
(6)

$$\Delta \lambda'' = -0.060698 + 2.719 E^{-7} \phi_{79}^2 \lambda_{79}^3 -$$

$$7.503 E^{-17} \phi_{79}^5 \lambda_{79}^7$$
(7)

where $\Delta \phi$ " and $\Delta \lambda$ " are obtained in arc of seconds, while ϕ and λ are the ELD79 coordinates in degrees.

Substitute the values of $\Delta \phi^{"}$ and $\Delta \lambda^{"}$ From (6) and (7) in the next equations to LGD2006 Geographic coordinates (latitude and longitude). The equations are:

$$\phi_{LGD\ 2006} = \phi_{ELD\ 79} + \Delta \phi'' \tag{8}$$

$$\lambda_{LGD \ 2006} = \lambda_{ELD \ 79} + \Delta \lambda'' \tag{9}$$

IV. COMPARISON OF BOTH TECHNIQUES

Four check points have been utilized to compare the validity of results which obtained from both transformation techniques. The coordinates of these stations have been computed through the final model for each technique, that are (three-parameter) Bursa-Wolf model and stepwise multiple regression approach. Then the transformed coordinates are be compared with the corresponding coordinates. The obtained results are presented in Tables II-V.

ACCURACY OF REGRESSION TECHNIQUE OVER CHECK POINTS			
Station	ϕ " observed	ϕ " computed	$\Delta \phi$ "(observed – computed)
1	14.32532	14.32545	-0.00013
2	2.39311	2.39649	-0.00338
3	21.3932	21.40995	-0.01675
4	47.38372	47.38908	-0.00536
Mean			0.006405
			0.1978 m

TABLE II

TABLE III			
ACCURACY OF REGRESSION TECHNIQUE OVER CHECK POINTS			
Station	λ " observed	λ " computed	Δλ"(observed – computed)
1	31.19265	31.20389	-0.01124
2	0.11685	0.12208	-0.00523
3	9.62358	9.61789	0.00569
4	20.61447	20.61293	0.00154
Mean			0.005925
			0.1830 m
Accur	TA ACVOE PUBSA WOL	BLE IV	CV DODITS
ACCUR	ACY OF BURSA-WOL	LF MODEL OVER CHI	ECK POINTS
Station	ϕ " observed	ϕ " computed	$\Delta \Phi$ "(observed – computed)
1	14.32532	14.32691	-0.00159
2	2.39311	2.39105	0.00206
3	21.3932	21.40546	-0.01226
4	47.38372	47.41510	-0.03138
Mean			0.0118225
			0.3651 m
TABLE V			
ACCURACY OF BURSA- WOLF MODEL OVER CHECK FOINTS			
Station	λ " observed	λ " computed	computed)
1	31.19265	31.21484	-0.02219
2	0.11685	0.1265	-0.00965
3	9.62358	9.60709	0.01649
4	20.61447	20.54543	0.06904
Mean			0.0293425
			0.9062 m

From Tables II and III, it can be seen that the overall accuracy of the developed multiple regression datum transformation technique is in the order of approximately 20cm in latitude and 7cm in longitude. Whereas the results obtained by using (three parameter) Bursa-Wolf model as illustrated in Table IV and V, show the accuracy found, is 33cm in latitude and 41cm in longitude. That means the developed multiple regression datum transformation technique is more accurate than the traditional similarity datum transformation technique. The reason for that is the disability of the similarity transformation models to represent the distortion existing in the old local geodetic networks. The same situation happens for several national and regional coordinate systems all over the world [1].

V.SURVEYING DEPARTMENT OF LIBYA TRANSFORMATION PARAMETERS

SDL utilized 29 control points over the country to produce transformation parameters between ELD79 and LGD2006 [7]. Those points have their coordinates in both datums.

For transformation parameters determination, the threeparameter Bursa-Wolf model has been used. The final transformation parameters are as follows:

$$\Delta X = +92.5515$$
 (10)

$$\Delta Y = + 10.8194 \tag{11}$$

$$\Delta Z = -149.8852 \tag{12}$$

Using the same check points to compare the results that obtained from this study (only three-parameter Buras-Wolf model) and SDL transformation parameters, these results are presented in Table VI and VII.

 TABLE VI

 ACCURACY OF SDL TRANSFORMATION PARAMETERS OVER CHECK POINTS

Station	ϕ " observed	ϕ " computed	$\Delta \phi$ "(observed – computed)
1	14.32532	14.34868	-0.02336
2	2.39311	2.41219	-0.01908
3	21.3932	21.42559	-0.03239
4	47.38372	47.43164	-0.04792
Mean			0.0306875
			0.9478 m

TABLE VII

ACCURACY OF SDL TRANSFORMATION PARAMETERS OVER CHECK POINTS			
Station	λ " observed	λ " computed	$\Delta \lambda$ "(observed - computed)
1	31.19265	31.20602	-0.01337
2	0.11685	0.11749	-0.00064
3	9.62358	9.59761	0.02597
4	20.61447	20.53649	0.07798
Mean			0.02949
			0.9108 m

From Table VI and VII, it can be seen that the accuracy is less than that found in Table IV and V. It was 95cm in latitude ad 70cm in longitude. The reason is that SDL utilized only 29 points distributed over the whole country to produce the transformation parameters.

VI. CONCLUSION

The coordinate transformation from ELD79 to the LGD2006 is currently an important issue in Libya. The obtained results show that the accuracy of stepwise multiple regression technique is better than the accuracy of traditional transformation technique. Consequently, it is recommended to be applied by using all available geodetic station, with a national coverage, to come up with an accurate set of regression equations to transform ELD79 coordinates into LGD2006 coordinates system. Also the results obtained show that the SDL transformation parameters isn't accurate

comparing with transformation parameters that obtained from this study.

ACKNOWLEDGMENT

The authors would like to acknowledge surveying department of Libya for providing some data set herein, also thanks to Engineer Said Alhamaly for his constructive criticism and stimulating discussion.

REFERENCES

- DMA Defense Mapping Agency, Department of Defense, "World Geodetic System 1984: Its Definition and Relationships with Local Geodetic Systems" (Second Edition). *Technical Report no.* 8350.2, Defense Mapping Agency, Washington, 1989.
- [2] G. Dawod and D. Alnggar "Optimum Geodetic Datum Transformation Techniques for GPS Survey in Egypt", Proceeding of AL-Azhar Engineering Sixth International Engineering Conference, volume 4, pp709-718, September 2000.
 [3] H. Wolf, "Geometric Connection and Re-Orientation of Three-
- [3] H. Wolf, "Geometric Connection and Re-Orientation of Three-Dimensional Triangulation Nets". *Bulletin Géodésique*, no. 68, pp. 165-169, 1963.
- [4] L.T. Applebaum, "Geodetic Datum Transformation by Multiple Regression Equations", *Proceedings of the Third International Geodetic Symposium on Satellite Doppler Positioning*, Las Cruces, New Mexico, pp.207-223, 1982.
 [5] M. Bursa, "The Theory for the Determination of the Non-Parallelism of
- [5] M. Bursa, "The Theory for the Determination of the Non-Parallelism of the Minor Axis of the Reference Ellipsoid and the Inertial Polar Axis of the Earth, and the Planes of the Initial Astronomic and Geodetic Meridians from Observations of Artificial Earth Satellites", *Studia Geophysica et Geodetica*, no. 6, pp. 209-214, 1962.
 [6] P. Zaletnyik," Coordinate Transformation with Neutral Network and
- [6] P. Zaletnyik," Coordinate Transformation with Neutral Network and with Polynomials in Hungary", Department of Geodesy and Surveying, Budapest,2004
- [7] SDL Surveying Department of Libya "Libyan Geodetic Datum 2006" Tripoli, Libya, 2006.
- [8] SDL Surveying Department of Libya "National Annual Report 2009", Tripoli, Libya, 2009.
- [9] W. E. Featherstone, "A Comparison of Existing Co-Ordinate Transformation Models and Parameters in Australia", Cartography, volume 26, no. 1, pp. 13-26, Australia, 1997.

Jamal A Gledan: Assistant professor at Department of Civil Engineering, Tripoli University Since 1994, He had his BSc in 1986 and MSc in 1994 at Tripoli University and finished his PhD at Newcastle University in 2004. He was the Director General of Surveying Department of Libya from 2006 to 2012. He is a member of consultant team at planning ministry since 2007

Othman A. Azzeidani: Msc student at Department of Civil Engineering, He had his BSc in 2007at Almargab University