Supercritical Methanol for Biodiesel Production from Jatropha Oil in the Presence of Heterogeneous Catalysts

Authors : Velid Demir, Mesut Akgün

Abstract : The lanthanum and zinc oxide were synthesized and then loaded with 6 wt% over γ -Al₂O₃ using the wet impregnation method. The samples were calcined at 900 °C to ensure a coherent structure with high catalytic performance. Characterization of the catalysts was verified by X-ray diffraction (XRD) and Fourier-transform infrared spectroscopy (FT-IR). The effect of catalysts on biodiesel content from jatropha oil was studied under supercritical conditions. The results showed that ZnO/ γ -Al₂O₃ was the superior catalyst for jatropha oil with 98.05% biodiesel under reaction conditions of 7 min reaction time, 1:40 oil to methanol molar ratio, 6 wt% of catalyst loading, 90 bar of reaction pressure, and 300 °C of reaction temperature, compared to 95.50% with La₂O₃/ γ -Al₂O₃ at the same parameters. For this study, ZnO/ γ -Al₂O₃ was the most suitable catalyst due to performance and cost considerations.

1

Keywords : biodiesel, heterogeneous catalyst, jatropha oil, supercritical methanol, transesterification

Conference Title : ICBB 2023 : International Conference on Biofuels and Bioenergy

Conference Location : Rome, Italy

Conference Dates : March 06-07, 2023