

## Instability of H<sub>2</sub>-O<sub>2</sub>-CO<sub>2</sub> Premixed Flames on Flat Burner

**Authors :** Kaewpradap Amornrat, Endo Takahiro, Kadowaki Satoshi

**Abstract :** The combustion of hydrogen-oxygen (H<sub>2</sub>-O<sub>2</sub>) mixtures was investigated to consider the reduction of carbon dioxide (CO<sub>2</sub>) and nitrogen oxide (NO<sub>x</sub>) as the greenhouse emission. Normally, the flame speed of combustion H<sub>2</sub>-O<sub>2</sub> mixtures are very fast thus it is necessary to control the limit of mixtures with CO<sub>2</sub> addition as H<sub>2</sub>-O<sub>2</sub>-CO<sub>2</sub> combustion. The limit of hydrogen was set and replaced by CO<sub>2</sub> with O<sub>2</sub>:CO<sub>2</sub> ratio as 1:3.76, 1:4 and 1:5 for this study. In this study, the combustion of H<sub>2</sub>-O<sub>2</sub>-CO<sub>2</sub> on flat burner at equivalence ratio  $\phi=0.5$  was investigated for 10, 15 and 20 L/min of flow rate mixtures. When the ratio of CO<sub>2</sub> increases, the power spectral density is lower, the size of attractor and cellular flame become larger because the decrease of hydrogen replaced by CO<sub>2</sub> affects the diffusive-thermal instability. Moreover, the flow rate mixtures increases, the power spectral density increases, the size of reconstructed attractor and cell size become smaller due to decreasing of instability. The results show that the variation of CO<sub>2</sub> and mixture flow rate affects the instability of cellular premixed flames on flat burner.

**Keywords :** instability, H<sub>2</sub>-O<sub>2</sub>-CO<sub>2</sub> combustion, flat burner, diffusive-thermal instability

**Conference Title :** ICMAME 2015 : International Conference on Materials, Automotive and Mechanical Engineering

**Conference Location :** London, United Kingdom

**Conference Dates :** January 19-20, 2015