

## **Wear Characteristics of Al Based Composites Fabricated with Nano Silicon Carbide Particles**

**Authors :** Mohammad Reza Koushki Ardestani, Saeed Daneshmand, Mohammad Heydari Vini

**Abstract :** In the present study, AA7075/SiO<sub>2</sub> composites have been fabricated via liquid metallurgy process. Using the degassing process, the wet ability of the molten aluminum alloys increased which improved the bonding between aluminum matrix and reinforcement (SiO<sub>2</sub>) particles. AA7075 alloy and SiO<sub>2</sub> particles were taken as the base matrix and reinforcements, respectively. Then, contents of 2.5 and 5 wt. % of SiO<sub>2</sub> subdivisions were added into the AA7075 matrix. To improve wettability and distribution, reinforcement particles were pre-heated to a temperature of 550°C for each composite sample. A uniform distribution of SiO<sub>2</sub> particles was observed through the matrix alloy in the microstructural study. A hardened EN32 steel disc as the counter face was used to evaluate the wear rate pin-on-disc, a wear testing machine containing. The results showed that the wear rate of the AA/SiO<sub>2</sub> composites was lesser than that of the monolithic AA7075 samples. Finally, The SEM worn surfaces of samples were investigated.

**Keywords :** Al7075, SiO<sub>2</sub>, wear, composites, stir casting

**Conference Title :** ICDMME 2024 : International Conference on Design, Mechanical and Material Engineering

**Conference Location :** Toronto, Canada

**Conference Dates :** September 19-20, 2024