World Academy of Science, Engineering and Technology International Journal of Biological and Ecological Engineering Vol:8, No:04, 2014

Cd2+ Ions Removal from Aqueous Solutions Using Alginite

Authors: Vladimír Frišták, Martin Pipíška, Juraj Lesný

Abstract : Alginate has been evaluated as an efficient pollution control material. In this paper, alginate from maar Pinciná (SR) for removal of Cd2+ ions from aqueous solution was studied. The potential sorbent was characterized by X-Ray Fluorescence Analysis (RFA) analysis, Fourier Transform Infrared Spectral Analysis (FT-IR) and Specific Surface Area (SSA) was also determined. The sorption process was optimized from the point of initial cadmium concentration effect and effect of pH value. The Freundlich and Langmuir models were used to interpret the sorption behaviour of Cd2+ ions, and the results showed that experimental data were well fitted by the Langmuir equation. Alginate maximal sorption capacity (QMAX) for Cd2+ ions calculated from Langmuir isotherm was 34 mg/g. Sorption process was significantly affected by initial pH value in the range from 4.0-7.0. Alginate is a comparable sorbent with other materials for toxic metals removal.

Keywords: alginates, Cd2+, sorption, QMAX

Conference Title: ICCEBE 2014: International Conference on Chemical, Environmental and Biological Engineering

Conference Location : Lisbon, Portugal **Conference Dates :** April 17-18, 2014