World Academy of Science, Engineering and Technology International Journal of Electronics and Communication Engineering Vol:8, No:07, 2014

Characterization of current-voltage (I-V) and capacitance-voltage-frequency (C-V-f) features of Au/GaN Schottky diodes

Authors: Abdelaziz Rabehi

Abstract : The current-voltage (I-V) characteristics of Au/GaN Schottky diodes were measured at room temperature. In addition, capacitance-voltage-frequency (C-V-f) characteristics are investigated by considering the interface states (Nss) at frequency range 100 kHz to 1 MHz. From the I-V characteristics of the Schottky diode, ideality factor (n) and barrier height (Φ b) values of 1.22 and 0.56 eV, respectively, were obtained from a forward bias I-V plot. In addition, the interface states distribution profile as a function of (Ess – Ev) was extracted from the forward bias I-V measurements by taking into account the bias dependence of the effective barrier height (Φ e) for the Schottky diode. The C-V curves gave a barrier height value higher than those obtained from I-V measurements. This discrepancy is due to the different nature of the I-V and C-V measurement techniques.

Keywords: Schottky diodes, frequency dependence, barrier height, interface states

Conference Title: ICECS 2014: International Conference on Electronics, Circuits and Systems

Conference Location: London, United Kingdom

Conference Dates: July 27-28, 2014