Neutronic Calculations for Central Test Loop in Heavy Water Research Reactor

Authors : Hadi Shamoradifar, Behzad Teimuri, Parviz Parvaresh, Saeed Mohammadi

Abstract : One of the experimental facilities of the heavy water research reactor is the central test loop (C.T.L). It is located along the central axial line of the vessel, and therefore will highly affect the neutronic parameters of the reactor, so from the neutronics point of view, C.T.L is the most important facility. It is mainly designed for fuel testing, thought other applications such as radioisotope production and neutron activation, can be imagine for it. All of the simulations were performed by MCNPX2.6. As a first step towards C.T.L analysis, the effect of D2O-filled, H2O-filled, and He-filled C.T.L on the effective multiplication factor (Keff.), have been evaluated. According to results, H2O-filled C.T.L has a higher thermal neutron, while He-filled C.T.L includes more resonance neutrons. In the next step thermal and total axial neutron fluxes, were calculated and used as the comparison parameters. The core without C.T.L (C.T.L replaced by heavy water) is selected as the reference case, and the effect of all other cases is calculated according to that.

1

Keywords : heavy water reactor, neutronic calculations, central test loop, neutron activation

Conference Title : ICNPPE 2017 : International Conference on Nuclear Power Plants Engineering

Conference Location : Bangkok, Thailand

Conference Dates : August 30-31, 2017