

## Preparation and Characterization of Hybrid Perovskite Enhanced with PVDF for Pressure Sensing

**Authors :** Mohamed E. Harb, Enas Moustafa, Shaker Ebrahim, Moataz Soliman

**Abstract :** In this paper pressure detectors were synthesized and characterized using hybrid perovskite/PVDF composites as an active layer. Methylammonium lead iodide (MAPbI<sub>3</sub>) was synthesized from methylammonium iodide (MAI) (CH<sub>3</sub>NH<sub>3</sub>I) and lead iodide (PbI<sub>2</sub>). Composites of perovskite/PVDF using different weight ratio were prepared as the active material. PVDF with weights percentages of 6%, 8%, and 10% was used. All prepared materials were investigated by x-ray diffraction (XRD), Fourier transforms infrared spectrum (FTIR) and scanning electron microscopy (SEM). A Versastat 4 Potentiostat Galvanostat instrument was used to perform the current-voltage characteristics of the fabricated sensors. The pressure sensors exhibited a voltage increase with applying different forces. Also, the current-voltage characteristics (CV) showed different effects with applying forces. So, the results showed a good pressure sensing performance.

**Keywords :** perovskite semiconductor, hybrid perovskite, PVDF, Pressure sensing

**Conference Title :** ICEMOM 2018 : International Conference on Electronic, Magnetic and Optical Materials

**Conference Location :** Dublin, Ireland

**Conference Dates :** July 23-24, 2018